

## nCite™ 1000 Session Border Controller



- **Leader in Security, Performance, Scale and Redundancy**
- **Enables the collapsing of multiple applications on a single platform**
- **Supports both B2BUA and Stateful Proxy models on the same platform**
- **Allows service layering architecture for Security, Oversubscription, QoS, Call Routing and IMS integration**
- **Supports unsurpassed Denial of Service (DoS) and Security for Signaling and RTP**
- **Provides protocol Interoperability and Media Transparency, Protocol and QoS Interworking Network Mediation**

The **nCite™ 1000** Session Border Controllers (SBCs) are designed and tested in conjunction with leading IP Communication Carriers and independent third party labs ensuring that products meet or exceed the functional and operational requirements of Service Providers globally. This cost-effective platform is designed for small, medium Service Providers and large enterprises. The nCite 1000 is optimized for operators that start to deploy VoIP hosted services or to interconnect their network with other VoIP carriers.

Session Border Controllers resolve the peering, latency, quality of service, capacity and control issues preventing widespread commercial deployment of VoIP. The SBC is a transparent addition to existing VoIP networks that enable Carriers and Service Providers to fully realize PSTN parity - resulting in a reduction of costs and increased revenue through the interconnection of VoIP islands. VoIP networks are typically built as "island networks" due to complexities associated with IP interconnection or peering (such as address overlap and security firewalls). The lack of scalability in current VoIP deployments is compounded by the lack of performance parity with the PSTN. Many indicators include the tremendous growth of IP PBXs and the adoption of VoIP and SIP-based products. nCite SBCs support three main application areas for wireline and wireless networks: Residential, Carrier to Carrier Peering and Enterprise.

nCite integrates both signaling and media in a single platform to securely and reliably deliver VoIP applications: voice, video and multimedia sessions across IP network borders.

### **nCite 1000 features Session Management/ Routing**

- Multiple B2BUA/Stateful Proxy
- Hosted Firewall and NAT (Traversal)
- Virtual Routing Domains
- H.323/SIP Interworking
- Advanced Routing capabilities
- ENUM/DNS
- Supports fragmented UDP/TCP
- Geographic Load Balancing

### **Security**

- Hardware-based DoS Protection
- Protocol Validation and fixup
- Media Firewall and Rogue RTP Detection
- Session-based Bandwidth Policing
- Topology Hiding
- SAC Policy per VPN/Customer
- IPSec, TLS
- Authentication based on source/destination IP address, domain, port, or protocol

# nCite™ 1000 Session Border Controller

## Specifications

### Capabilities

Performance	<ul style="list-style-type: none"><li>• Up to 4,000 concurrent sessions</li><li>• One Gbps bandwidth</li><li>• Less than 31 microseconds latency</li></ul>
High Availability	<ul style="list-style-type: none"><li>• Supports Active/Stand-by or Active/Active configurations</li><li>• Geographic Redundancy supported across WAN links</li><li>• Uninterrupted service in the case of device or link failure</li><li>• Hitless software upgrade (no call or media failure)</li></ul>
Management	<ul style="list-style-type: none"><li>• Element Management System</li><li>• API Interface</li><li>• SNMP v2c</li><li>• XML</li><li>• Advanced Logging Capabilities</li><li>• Dynamic Configuration Changes</li><li>• Per Call Jitter and Packet Loss Reporting</li></ul>
Operations	<ul style="list-style-type: none"><li>• RADIUS Authentication</li><li>• Detail Records for Sessions, Registrations and Call Failures</li><li>• Real-Time Monitoring of Subscribers and Sessions</li><li>• Detailed Statistics Logging</li><li>• Off-Board Logging – Syslog</li><li>• CALEA</li></ul>

### Hardware

Physical	Dimensions: 1.70" x 16.93" x 20" (43.25 mm x 430 mm x 508 mm) Weight: 25 lbs (11.3 kg) Operation temp: 32F - 131F (5C - 50C) Humidity: 5%-85% non-condensing Heat dissipation: 1200 BTU/hour RoHS: Complies with RoHS directive 2002/95/EC
----------	---

### Power requirements

#### DC Power Supply

Max Power: 560 W  
Voltage Range: -38 VDC to -75 VDC  
Maximum Current:  
11.7 A @ -48 VDC  
9.3 A @ -60 VDC

#### AC Power Supply

Max Power: 630 W  
110 Operation: 100 VAC to 127 VAC  
47 to 63 Hz  
6.3 A Max at 100 VAC  
220 Operation: 200 VAC to 240 VAC  
47 to 63 Hz  
3.2 A Max at 200 VAC

### Applications

- Hosted Residential Services
- Carrier to Carrier VoIP Peering
- Hosted Enterprise Services
- SIP H.323 Interworking Gateway

### About Nuera Communications

Nuera Communications, designs, manufactures & sells packet voice gateways to communication service providers worldwide. These products work over any medium (cable, wireless, copper and fiber). Nuera's ORCA (Open Reliable Communications Architecture) product portfolio of VoIP gateways, softswitches, and management systems provide telephony solutions for cable and DSL networks, international long distance networks and enterprise networks. Nuera is a leader in the broadband telephony market.

### Nuera Communications Inc. Asia Pacific / Middle East Office

371 Beach Road, KeyPoint #08-07  
Singapore 199597  
Tel: +65-6391-9030  
Fax: +65-6299-4925

### US Office

9890 Towne Centre Drive, Suite 150  
San Diego, CA 92121, USA  
Tel: +1-858-625-2400  
Fax: +1-858-625-2422

Website: [www.nuera.com](http://www.nuera.com)

©2008 Nuera Communications, Inc. All rights reserved. Nuera, the Nuera logo and the other trademarks noted above are trademarks and registered trademarks of Nuera Communications, Inc.

Ref. # LTRM-04011 V.2 05/08



NUERA®